



Daemon3D Print

Address Unit 19, Barnwell Business Park
Barnwell Drive
Cambridge
CB5 8UZ

Phone +44 (0) 1223 213756

Email sales@daemonprintsupplies.com

Web www.daemon3dprint.com

V6 Assembly

Introduction

V6 Assembly is easy, and we provide most of the tools you'll need. Note, though, that you should be very careful of the following safety cautions:

- Be aware of your electronics. Don't work on your printer while it is plugged in or turned on.
- Be aware when you heat up your new hotend not to burn yourself.

Tools

- Multimeter
- Hex Wrench
- Screwdriver
- Nozzle Spanner

Parts

- V6 Heatsink
- V6 Heat Break
- V6 Heater Block
- V6 Nozzles
- Thermistor Cartridge
- Heater Cartridge
- 30mm Fan
- Plastic Screws x 4
- M3 Grub Screw
- Fan Duct
- M3 Washer
- M3x10 Socket Dome Screw
- V6 Silicone Sock
- Collet
- Collet Clip
- Silicone sock



Daemon3D Print

Address Unit 19, Barnwell Business Park
Barnwell Drive
Cambridge
CB5 8UZ

Phone +44 (0) 1223 213756

Email sales@daemonprintsupplies.com

Web www.daemon3dprint.com

Step 1.) Assemble Nozzle and Heat Break

You'll need the following parts:

- Heater Block
- Nozzle
- Heat Break

Step 2.) Orient your Heater Block

Before starting work on your heater block, make sure that you'll going to screw your nozzle into the correct side.

- You should be looking at the side of the heater block with three holes in it

Step 3.) Screw in Nozzle

- Screw in the nozzle all the way into the heater block. Don't worry about tightness yet.
- Then, unscrew the nozzle by a 1/4 of a turn. This will leave a little space to tighten after screwing in the heat break.

Step 4.) Screw in Heat Break

- Screw in the heat break until it touches the nozzle.
- Tighten the nozzle against the heat break. No need to over tighten, we'll be hot-tightening later.

Step 5.) Heat Break Check

Double check that your nozzle is still almost flush with your heater block.

- If there is significant space between the nozzle top and the heater block you should re-adjust your nozzle and heat break to eliminate that space.

Step 6.) Gather Thermistor Parts

Gather the parts you'll need to install the thermistor:

- Thermistor Cartridge
- M3 Grub Screw
- The smaller, 1.75mm Hex Wrench
- Heater Block



Daemon3D Print

Address Unit 19, Barnwell Business Park
Barnwell Drive
Cambridge
CB5 8UZ

Phone +44 (0) 1223 213756

Email sales@daemonprintsupplies.com

Web www.daemon3dprint.com

Step 7.) Slide in Thermistor

- Slide in the thermistor cartridge.

You can slide the cartridge in either direction so that the wires extend from one side or the other of your heater block. Think about how you'll be organising your wiring to decide which makes sense for your printer.

Step 8.) Screw in Grub Screw

- Screw in grub screw until it just touches the thermistor.
- Tighten M3 grub screw by an 1/8 of a turn.

Do not over tighten the screw. The thermistor cartridge is soft, and you might deform it if you over-tighten the screw.

Step 9.) Test Heater Cartridge

- Before you install your heater cartridge, you should double check that you both purchased and received the correct voltage cartridge. Cartridges are laser etched with their voltage, but all it is worth double-checking anyway. *This process is less annoying than putting out a house fire.*
- If you have a 12v30w heater cartridge, your multimeter should read 4.8Ω
- If you have a 24v30w heater cartridge, your multimeter should read 19.2Ω
- Your cartridges resistance may deviate slightly from these numbers, which is fine. We're mostly interested in verifying which cartridge type you have.

Step 10.) Gather Heater Cartridge Parts

Gather the parts you'll need to install your heater cartridge:

- Heater Block
- Heater Cartridge
- The larger 2.5mm Hex Wrench
- One of the longer M3x10 Screws and M3 Washer

Step 11.) Slide in Heater Cartridge

- Slide in the heater cartridge. Typically, you'd want the wires to come out the same side as your thermistor wires.
- It's fine if the cartridge protrudes a bit from both sides of the heater block.



Daemon3D Print

Address Unit 19, Barnwell Business Park
Barnwell Drive
Cambridge
CB5 8UZ

Phone +44 (0) 1223 213756

Email sales@daemonprintsupplies.com

Web www.daemon3dprint.com

Step 12.) Screw in M3 x 10 Screw

- Tighten the M3 x 10 socket dome screw (with the M3 washer on it) with 2 mm hex key until the clamp deforms slightly.

Step 13.) Tug Test

- Before moving on, gently tug on your thermistor and heater cartridge wires. We don't want them slipping out during a print!

Step 14.) Gather Parts for the Heatsink

Gather the following parts:

- Heater Block
- Heatsink
- Thermal Paste Sachet

Step 15.) Apply Thermal Compound

- Apply thermal compound the thread of the heat break. You don't need to use the whole sachet.
- After you're done, screw in the heatsink. It only needs to be hand-tight.

Don't use any thermal paste elsewhere on your hotend

Wash your hands once you're done working with the paste

Step 16.) PTFE Tubing

Gather the following parts:

- Assembled Hotend
- Collet
- Collet Clip
- PTFE Tubing (at least 70cm long)

Step 17.) Insert Collet

- Insert the small black collet into the top of the Heatsink, the side with the four small legs should push into the brass ring in the top of the heatsink with gentle finger pressure.
- Slip the collet clip underneath the collet, holding it up.



Daemon3D Print

Address Unit 19, Barnwell Business Park
Barnwell Drive
Cambridge
CB5 8UZ

Phone +44 (0) 1223 213756

Email sales@daemonprintsupplies.com

Web www.daemon3dprint.com

Step 18.) Prep PTFE Tubing

- To make sure that the end of the PTFE tubing that will sit inside your hotend is square and flat, cut a slice off with a very sharp knife (a craft knife with razor sharp blade is recommended for this).

Step 19.) Insert PTFE and Lock in Place

- Insert the PTFE tubing. The collet clip should pre-tension the tubing and lock it into the hotend; the tubing should be held securely downwards without any ability to wiggle or move.
- To release, remove the collet clip, and push down on the collet while pulling the tubing.

Step 20.) Fan and Duct Parts

Gather the following:

- Hotend
- 30mm Fan
- 4 Plast-fast Philips-head Self-tapping Screws
- Fan Duct

Step 21.) Screw Plastfast Screws into Fan

Make sure the screw heads are on the non-sticker side on the fan.

- Screw the Plastfast screws partially into the fan.

The screws should not be sticking out of the opposite side yet.

Step 22.) Screw Fan into Fan Duct

Think about where you want your fan's wires to come out before screwing it on. (You can mount the fan duct facing either way on your HotEnd)

- Screw the fan onto the fan duct. You may require a lot of torque and will therefore need a good fitting screwdriver.
- Don't worry about getting the screws 100% tightened, you just need to secure the fan.



Daemon3D Print

Address Unit 19, Barnwell Business Park
Barnwell Drive
Cambridge
CB5 8UZ

Phone +44 (0) 1223 213756

Email sales@daemonprintsupplies.com

Web www.daemon3dprint.com

Step 23.) Clip Fan Duct onto Heatsink

- Clip the duct onto heatsink

Make sure the duct covers the fin closest to the heater block.

- The little over-hang can face up, down, depending on your setup.

Step 24.) Connect Extension Wires

- Plug the extension wires into your thermistor and fan. The other ends will go into your printer's electronics board.

If you're replacing an old HotEnd, note where its wires were plugged in and mirror those for your new V6.

If you're building a new printer, you may need to consult the documentation for your electronics board to see where to plug in everything.

- Use the included cable tie to link the connections together for strain relief.

Take a little while to properly organise your wiring so that it doesn't get snagged on any corner of your printer.

Step 25.) Firmware

Configuring your firmware is different depending on the type your printer uses.

- Marlin
- Repetier
- Smoothieware
- RepRap Firmware

Step 26.) PID Tuning

Whenever you install a new hotend, it's important to run a PID tune. This will allow your printer to adjust some internal parameters so that it can learn how your hotend heats up. This way, your printer can anticipate how much power it needs to give your hotend to get it up to temperature, but not over.

- Use a computer to connect to your printer. If you have a typical RepRap printer, you can use PrintRun, Repetier Host, Simplify3D, or MatterControl.
- Other, closed-source, printers may be better suited to their manufacturer's recommended printer control software.



Daemon3D Print

Address Unit 19, Barnwell Business Park
Barnwell Drive
Cambridge
CB5 8UZ

Phone +44 (0) 1223 213756

Email sales@daemonprintsupplies.com

Web www.daemon3dprint.com

Step 27.)

Make sure you have your hotend in a place where it can get hot without damaging anything or setting any fires! Mounted on your printer or held with a spanner will work fine. Take care not to touch your hotend when it heats up.

- Send the command M303 to autotune your PID.

Not all firmware support PID autotuning, and you may need to tune manually.

- We recommend running two PID tunes for the V6, one now and one later at at normal printing temperatures, with filament in the hotend, sock attached, and with an active cooling fan on if you're planning on using one. This way your printer can finely tune its settings to match your real printing environment.

Step 28.) Hot-Tightening

- Hot-tightening is the last mechanical step before your V6 is ready to go! Hot-tightening is essential to sealing the nozzle and heatsink together to ensure that molten plastic cannot leak out of the hotend in use.
- Using your printer's control software (or LCD screen), set the hotend temperature to 270°C. Allow the hotend to reach 270°C and wait one minute to allow all components to equalise in temperature.
- Gently tighten the nozzle whilst holding the heater block still with a spanner and using a smaller 7mm spanner to tighten the nozzle. This will tighten the nozzle against the Heatsink and ensure that your hotend does not leak.
- You want to aim for 3Nm of torque on the hot nozzle—this is about as much pressure as you can apply with one finger on a small spanner.

Step 29.) Gather Sock Parts

Gather the following:

- Silicone Sock, one of either:
 - Pro Sock
 - Or Normal Sock
- Your HotEnd

Step 30.) Attaching Sock

- First, let your hotend cool down.
- Slip your silicone sock over the hotend. Try to get each of the little clips on the top of the heat block so the sock will stay on better.

It may look like your sock doesn't quite fit. Don't worry, when you heat up your HotEnd, the sock will expand, and the clips will fit just fine.



Daemon3D Print

Address Unit 19, Barnwell Business Park
Barnwell Drive
Cambridge
CB5 8UZ

Phone +44 (0) 1223 213756

Email sales@daemonprintsupplies.com

Web www.daemon3dprint.com

Step 31.) Final Adjustments

- If you're using the pro sock make sure that the tip of the nozzle protrudes from the sock.

Step 32.) Congratulations

You're now ready to go! Remember you'll have to update your slicer settings a little:

- Check your nozzle diameter in your slicer. All V6 kits ship with a 0.40mm brass nozzle.
- Having very long retraction settings will cause problems.
 - For direct extrusion systems you should use anywhere from 0.5mm–1.0mm of retraction.
 - For bowden systems you can use up to 2.0mm of retraction.
- Print PLAs at 205–215°C, and ABS at ~240°C. For other materials check with their manufacturer